Genesis

Clean • Quiet • Effortless

Features

- Sealed precision bearings in swivel and wheel provide quiet, effortless mobility
- Soft (65A), non-marking MonoTech wheels reject debris and are excellent on both carpet and hard floors
- Strong protective body conceals components for easy cleaning
- Integrated thread guards protect wheels from entangling debris

Applications

- Computer Carts
- Laboratory Equipment
- Audio/Video Carts
- Electronic Equipment
- Seating
- Medical Carts
- Monitoring Equipment Stands
- IV Poles

Options

- Integrated Tread Brake: Available on all models.
- **Central Locking** Total Lock Brake available by special order; contact factory for details.
- Custom Colors available by special order; contact factory for
- Additional Fastenings: Does your application require a metric or special fastening? Please contact us for minimums and availability.



Wheel Selection

Floor Protection Non-Marking

Quiet/Cushion Roll

Chemical Resistance

Durability



| MonoTech - |
|------------|
| √ + |
| √ + |
| √ + |
| √ + |

MonoTech Facts

- 1. Provides ultimate floor protection and a quiet, cushioned ride.
- 2. Rolls over obstacles with ease.
- 3. Will not flat spot and is excellent on any floor type.
- 4. Rejects floor debris, including metal shavings and glass.

| Wheel Diameter (Inches) | Width | Height | Swivel Radius (Inches) | Tread Type | Finish | Dynamic Load (Pounds) | Swivel Base Model Number (Add fastening code) | Tread Brake Model Number (Add fastening code) | Fastening Selection* |
|-------------------------------|-------------------|--------------------------|------------------------------|---|---|--|---|--|---|
| 3" | 1" | 4" | 2-15/16" | MonoTech | White | 110 | PGE30WH-MNT33(GG) | PGE30WH-MNT33(GG)B | Threaded: |
| | | | Brake: | MonoTech | Grey | 110 | PGE30GR-MNT33(GG) | PGE30GR-MNT33(GG)B | 507, 605, 637, 748 Grip Ring: 223, 211 |
| | | | 3-3/4" | MonoTech | Black | 110 | PGE30BK-MNT33(KK) | PGE30BK-MNT33(KK)B | Hollow Kingpin: 403 |
| 4" | 1-1/4" | Stem: | 3-3/4" | MonoTech | White | 225 | PGE40WH-MNT63(GG) | PGE40WH-MNT63(GG)B | Threaded: 741, 748 |
| | | Plate: 5-5/8 " | Brake: 4-1/8" | MonoTech | Grey | 225 | PGE40GR-MNT63(GG) | PGE40GR-MNT63(GG)B | Grip Ring: 291 Plate: 120 Hollow Kingpin: 400 |
| | | | | MonoTech | Black | 225 | PGE40BK-MNT63(KK) | PGE40BK-MNT63(KK)B | |
| | Diameter (Inches) | Diameter (Inches) 3" 1" | Name Continue | Diameter (Inches) Width (Inches) Height (Inches) Radius (Inches) 3" 1" 4" 2-15/16" Brake: 3-3/4" 3-3/4" 5-3/8" Plate: 4-1/8" 3-3/4" | Diameter (Inches) Width (Inches) Height (Inches) Radius (Inches) Tread Type | NonoTech Stem: Stem: S-3/8" Plate: NonoTech Stem: S-3/8" Plate: NonoTech Stem: S-3/8" Plate: NonoTech Stem: S-3/8" NonoTech NonoTech NonoTech NonoTech NonoTech NonoTech NonoTech Nono | Diameter (Inches) Width (Inches) Radius (Inches) Tread Type Finish (Pounds) | Diameter (Inches) Width (Inches) Height (Inches) Radius (Inches) Tread Type Finish Load (Pounds) Swivel Base Model Number (Add fastening code) | 1 |

*To order, include **blue** fastener code in **Base Model Number**. Example: PGE30507WH-MNT33(GG) Top Plate **Threaded Stem Grip Ring Hollow Kingpin** 291 605 223 403 or 400 2-3/4 1-1/4" to 3" 7/16"

Socket Options

5/16"

Shepherd has many solutions to help you mount your casters to your equipment quickly and easily. See pages 56-57 for more information.













